## Page 1/2

## **GRAIN SIZE ANALYSIS DATA SHEET - HYDROMETER**

**ASTM D7928** Sample \_\_\_\_\_

<b>PROJEC</b>	T										Gample	
Project No												
Date Tested: Date Sampl				ed			Date Received:					
Boring No.: Sample			e No.:	Elevation	Elevation/depth:		Sample Length:		Test Re	Test Requested By:		
Location:												
Description	n/visual Clas	sificatior	1:									
□ Bulk □	SPT 🗆 Thir	n wall 🗆	l Other:									
SPECIMI	EN AND E	QUIPN	IENT DATA									
Prior Testing ☐ No ☐ Yes Sp. Gravity: ☐ Assumed ☐				Measured Balance ID Oven ID:						nometer ID: Vash Sieve ID:		
Separation	n Sieve: □ N	o. 10 or:	Spec	cimen Prep Method: ☐ Moist ☐ A				Air Drie	ed Companion D 6913:			
Estimated	Moisture	Mass of	Moist Soil	Dry Mass of Soil:								
and Mass: M <sub>m</sub> +Tare			(g)				Method: □ D			Pirect Method:		
f <sub>est</sub> (%):	<del>-</del>	Tare (g)								re No.:		
f <sub>est</sub> (%): M <sub>mest</sub> g):	r	M <sub>m</sub> (g)։_	N.41	Wet soil & tare (g): Dry soil & tare (g):					M <sub>dd</sub> & tare (g):			
M <sub>mest</sub> = H <sub>c</sub> x (100 /	% fines est) x	-	n Mixing	Tare (g):					M <sub>ed</sub> (g):			
(1 + (w <sub>cet</sub> Hc = 45 for 151, §	55 for 152	Jontaine	er ID:	Water Content (%): Dry Mass, $M_d$ (g) = $M_{dd}$ - $M_{disp}$						$M_{dd}$ - $M_{disp}$		
				Dry Mass, M <sub>d</sub> (g):								
Dispersed	e: ☐ cup & mixer ☐ air jet @ 69 kPa (sand) ☐ air jet @ 172 kPa (clay)											
Mixing Me	Amount of Dispersant, M <sub>disp</sub> (g) Direct Add: □ Dispersed in 100 ml w											
Temperatu	Cyl. □ Calib. Relationship				Foam inhibitor used: ☐ Yes ☐ No							
Temperatu	namber/Water bath Floccula					ation? □ Yes □ No						
С	No. 200 Wash Information											
Temp.°C	Reading, F	R <sub>151/152</sub>	A/B	Oven Drying Container ID:								
				Container Mass, (g):								
		Dry Mass Retained after Washing + tare, (g):										
Dry Mass Retained after Washing over No. 200, M <sub>dr</sub> (g):							00, M <sub>dr</sub> (g):					
Percent passing No. 200 (%) = (1-(M <sub>dr</sub> / M <sub>d</sub> )) x 100%:												
					n Data							
Ave. A or	Hydrometer ID: $\Box$ 151H $r_1 = 0.995$ $r_2 = 1.038$ $H_{r1} = $ $H_{r2} = $											
Std. Dev.=				$\Box$ 152H $r_1 = -5$ $r_2 = 60$ $H_{r1} = \frac{r_1}{r_1} = \frac{r_2}{r_2} = \frac{r_2}{r_1}$						H <sub>r2</sub> =		
			direct graduated cylinder, V <sub>hb</sub> = Vol <sub>2</sub> - Vol <sub>1</sub>									
Amount of dispersant used in calibration solution (g):				Submerge Volume	Submerged Volume		$\mathbf{V}_{hb} = \underline{\qquad} - \underline{\qquad} = \underline{\qquad} cc$ $\Box$ indirect water displacement, $V_{hb} = W_{w}(g) / 1 (g/cc)$ $\mathbf{V}_{hb} = \underline{\qquad} cc$					

SPECIMEN AND EQUIPMENT DATA (cont.)  Starting Date:  Starting Time:										Sample			
Starting Date:					Δ	£:4:							
Sedimentation Cylinder  Vol of					Annex A1 Sedimentation Cylinder Specifications								
ID:	Suspensi	on		Minimum			Maximum				Annex A1 Pass/Fail		
Inside Area, A <sub>c</sub> (cm²):					22.9 32.2						☐ Pass ☐ Fail		
Is the sample a subspecimen? □ Yes □ No				Percent passing the separation sieve (2 decimal place									
HYDRO	/IETER TI	EST DAT	A										
Time Date	Elapsed Time, T	Temp	ilip	ometer Reading r <sub>m</sub>		□ Calibr	anion	Effective Depth, H <sub>m</sub>			D	Mass Percent (%)	
	(min)	(°C)	151H 0.	001's	Actual	Offse	t, r <sub>d,m</sub>		(cm)	(mm)		Finer, N <sub>m</sub>	
									I				
Describe	if any mateı	rial was exc	cluded a	nd if	any problems	were enc	ountere	ed:				l:	
Notes:													
		· · · · · · · · · · · · · · · · · · ·										_ 20.10.19	
Tested by:													
	Ву:			Dat	te:								
Checked By:			Date:			Ti	itle:						