

DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers

PROJECT INFORMATION

Concrete Proportions and Properties

Project: Coast Isle Mall - Phase II
Salisbury Beach

Architect: Johnson, Jones & Associates, PC
New York, NY

Engineer: Lake City Design Associates, Inc.
Lake City, New York

Contractor: Allison-Barton Construction Co.
Salisbury Beach, Connecticut

Testing
Laboratory: New England laboratories, inc.
Salisbury Beach, Connecticut

Remarks: Concrete supplied from plant number 4

Mix Number 3000-D4

Design Strength 4000

Design Age 28

Supplier:

Ideal type II Portland cement 6.2 sacks/cy

#67 Aggregate - Brown Brothers C33 1775 lbs/cy

Sand - Brown Brothers C33 1245 lbs/cy

Water (5.48 gal./sack) 34 gal/cy

AE - Masterbuilders (MB-AE10) as required

DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers

Report Number	DATE OF TEST	CYLINDER STRENGTHS, psi			Slump in.	Air Content %	Conc Temp	Ave Test Value	Cumul Ave	Cumul S D	Cumul C V	Move 15 S D	Move 15 C V	Move 5 Ave	Range of Test	Cumul Ave Range	Mov 5 Range	W/In Test C V
67	7/22/2008	4360	4510	4490	3.25	4.5	67	4453	4453	---	---	---	---	---	150	150	---	1.99
69	7/22/2008	4250	4300	4320	3.75	5.1	70	4290	4372	115	2.6	---	---	---	70	110	---	1.49
72	7/22/2008	4450	4420	4410	3.50	5.3	72	4427	4390	88	2.0	---	---	---	40	87	---	1.17
73	7/22/2008	4210	4300	4290	4.25	5.5	70	4267	4359	94	2.2	---	---	---	90	88	---	1.19
76	7/22/2008	4460	4470	4400	4.00	5.6	69	4443	4376	90	2.1	---	---	4376	70	84	84	1.13
78	7/22/2008	4100	4190	4180	3.75	3.5	55	4157	4339	120	2.8	---	---	4317	90	85	72	1.16
79	7/22/2008	4290	4200	4210	4.25	4.9	65	4233	4324	117	2.7	---	---	4305	90	86	76	1.17
81	7/22/2008	3940	3980	3960	5.50	6.0	65	3960	4279	168	3.9	---	---	4212	40	80	76	1.10
82	7/22/2008	4210	4250	4220	4.25	4.9	58	4227	4273	158	3.7	---	---	4204	40	76	66	1.04
84	7/22/2008	4350	4420	----	4.50	5.4	62	4385	4284	153	3.6	---	---	4192	70	75	66	1.07
87	7/22/2008	4600	4520	4580	5.50	5.6	68	4567	4310	169	3.9	---	---	4274	80	75	64	1.07
88	7/22/2008	4550	4490	4500	4.25	3.9	59	4513	4327	171	4.0	---	---	4330	60	74	58	1.04
89	7/22/2008	4200	4250	4400	4.75	4.8	65	4283	4323	164	3.8	---	---	4395	200	84	90	1.18
91	7/22/2008	4320	4350	4390	4.00	4.9	71	4353	4326	158	3.7	---	---	4420	70	83	96	1.16
92	7/22/2008	4410	4480	4350	3.75	2.5	56	4413	4331	154	3.6	154	3.5	4426	130	86	108	1.20
94	7/22/2008	4290	4190	4260	4.50	6.0	75	4247	4326	150	3.5	152	3.5	4362	100	87	112	1.21
96	7/22/2008	4410	4450	4290	3.75	5.8	68	4383	4330	146	3.4	152	3.5	4336	160	91	132	1.27
97	7/22/2008	4750	4800	4720	3.00	4.2	71	4757	4353	174	4.0	188	4.2	4431	80	91	108	1.25
98	7/22/2008	4320	4400	4420	4.50	5.0	58	4380	4355	169	3.9	187	4.2	4436	100	91	114	1.26
99	7/22/2008	4280	4270	4000	3.50	5.2	61	4183	4346	169	3.9	190	4.3	4390	280	101	144	1.39

DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers

Report Number	DATE OF TEST	CYLINDER STRENGTHS, psi			Slump in.	Air Content %	Conc Temp	Ave Test Value	Cumul Ave	Cumul S D	Cumul C V	Move 15 S D	Move 15 C V	Move 5 Ave	Range of Test	Cumul Ave Range	Mov 5 Range	W/In Test C V
101	7/22/2008	4600	4590	4550	3.25	4.8	62	4580	4357	172	4.0	193	4.3	4457	50	98	134	1.35
102	7/22/2008	4420	4480	4450	3.75	5.1	68	4450	4361	169	3.9	190	4.3	4470	60	96	114	1.33
103	7/22/2008	4100	4150	4190	4.75	6.3	75	4147	4352	172	3.9	165	3.8	4348	90	96	116	1.32
105	7/22/2008	4290	4350	4380	3.75	5.8	70	4340	4352	168	3.9	160	3.7	4340	90	96	114	1.32
106	7/22/2008	4280	4350	4270	4.00	5.0	65	4300	4350	165	3.8	162	3.7	4363	80	95	74	1.31
107	7/22/2008	4310	4360	4380	4.75	5.2	67	4350	4350	161	3.7	155	3.6	4317	70	94	78	1.30
109	7/22/2008	4390	4450	4460	4.50	6.0	66	4433	4353	159	3.7	151	3.5	4314	70	93	80	1.28
110	7/22/2008	4760	4680	4650	3.25	5.0	71	4697	4365	169	3.9	170	3.8	4424	110	94	84	1.29
111	7/22/2008	4500	4550	4380	5.25	5.2	68	4477	4369	167	3.8	171	3.8	4451	170	97	100	1.32
112	7/22/2008	4290	4350	4360	4.50	5.8	58	4333	4368	164	3.8	172	3.9	4458	70	96	98	1.31
113	7/22/2008	4460	4430	4390	5.50	4.9	59	4427	4370	162	3.7	166	3.7	4473	70	95	98	1.30
115	7/22/2008	4100	4090	4120	6.75	6.0	50	4103	4361	166	3.8	185	4.2	4407	30	93	90	1.27
116	7/22/2008	4250	4200	4210	5.75	5.4	64	4220	4357	165	3.8	161	3.7	4312	50	92	78	1.25
118	7/22/2008	4350	4390	4250	4.75	5.6	79	4330	4356	163	3.7	161	3.8	4283	140	93	72	1.27
119	7/22/2008	4270	4200	4190	4.50	5.0	68	4220	4352	162	3.7	158	3.7	4260	80	93	74	1.27
120	7/22/2008	4420	4390	4350	5.00	4.8	59	4387	4353	160	3.7	146	3.4	4252	70	92	74	1.26

DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers

Report Name: demo4 report
 Report Description: sample
 Report File: Demo4.SRC

Analysis Criteria

Project(s): Coast Isle Mall - Phase II
 Mix(es): 3000-D4
 Supplier: use all
 Technician: use all
 Slump filter: No lower limit to no upper limit
 Air Content filter: No lower limit to no upper limit
 Temperature filter: No lower limit to no upper limit
 Test dates: 1/1/1900 to : 11/19/2008
 Specimen age: 28 days

Analysis Results (28 days)

Number of tests -----	36	
Standard Deviation Adjustment Factor (ACI 301-05) -----	1.000	per Table 4.2.3.3.b
Average strength -----	4353 psi	
Standard deviation -----	160 psi	
Adjusted standard deviation -----	160 psi	per Table 4.2.3.3.b
1.000 x 160 = 160 psi		
Design strength (28 days) -----	4000 psi	
Minimum required average strength (ACI 301-05) -----	4220 psi	per Table 4.2.3.3.c
1.34 x 160 + 4000 = 4214 psi		
2.33 x 160 + 4000 - 500 = 3873 psi		
Margin of extra performance -----	133 psi	
(Average strength - minimum required average strength)		
Probability of a test below 4000 based on normal distribution is 1.36%		
Probability of a test below 3500 based on normal distribution is 0.00%		
Concrete performance (ACI 214R-02) -----	Excellent	per Table 3.2
Based on standard deviation of 160 psi		
Using laboratory trial batch rating system		
Laboratory testing proficiency (ACI 214R-02) -----	Excellent	per Table 3.2
Within test coefficient of variation -----	1.26	
Using laboratory trial batch rating system		
Average range -----	92 psi	
Maximum 2 specimen range permitted to attain a rating of good: --	238 psi	
Maximum 3 specimen range permitted to attain a rating of good: --	357 psi	

The above statistical analysis will also qualify mixes

Mix ID: _____
 Strength: _____


DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers


Report Name: demo4 report
 Report Description: sample
 Report File: Demo4.SRC

28 Day Strengths (o) and 5 Test Moving Average (+)

Specified Strength: 4000 (denoted by)
 Required Strength: 4220 (denoted by - - - -)



28 Day Strength Distribution



99% Confidence value = 3981 psi


DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers

Report Name: demo4 report
 Report Description: sample
 Report File: Demo4.SRC


15 Test Moving Standard Deviation - 28 Day Test Strength

Standard Deviation:	Below 400	400-500	500-600
ACI 214R-02 Rating:	Excellent	Very good	Good
Line symbol used:	- - - -	- - - -



Estimated 28 Day Within Batch Coefficient of Variation (+) Moving Average Range of 5 28 Day Tests (o)

Within Batch Coefficient of Variation:	Below 3	3-4	4-5
ACI 214R-02 Rating:	Excellent	Very good	Good
Line symbol used:	- - - -	- - - -



DOCUMENTATION OF CONCRETE MIX PERFORMANCE

AMT Engineers

Report Name: demo4 report

Report Description: sample

Report File: Demo4.SRC

28 Day Strength (o) - Slump (+) - Air Content (x)

